



LEFT OUTSIDE VIEW

RIGHT INSIDE VIEW
SCALE - 1"=1"

RIGHT INSIDE VIEW
SCALE - 1"=1"

CUT HOLES FOR BEARING
BRACKET BOLT HEADS
(AT ASSEMBLY)

RS-19, BEVEL FLUSH
WITH TOP OF RIB

RS-19, BEVEL FLUSH WITH TOP
OF RIB

RS-0 CORNER
BLOCK

ALUM. CHANNEL
CARRY THROUGH

RS-0 CORNER
BLOCK

SUPPORT
POST (TYR.)

SUPPORT POST

AN3-13A BOLT (2)
AN365-1032 NUT (2)
AN970-3 WASHER (2)

STATION 2, 41 3/4"

1/8" MAH. PLY CAP BETWEEN
WING SUPPORT POST (CUT
FROM SCRAP)

STATION 4, 70"

CUT OUT FUSELAGE SIDE
PLY. FOR SUPPORT POST
PLY. (FRONT AND REAR)

RS-8 (PLY
BACKING)
CORNER GUSSET
(SEE DWG. NO. 4)



1992

DATE: 3-17-92

SCALE: 1"=1"

MODEL NO. 1700

DWG. TITLE: FUSELAGE CONST.

DWG. NO. 9